

## Silicone Heater Hose

# HH



Hotstart/Flexfab silicone heater hose is the flexible and durable plumbing solution specifically designed for installation on standby generators with Hotstart coolant engine heaters.



### RELIABLE COOLANT HEATING

Hotstart/Flexfab silicone heater hose is resistant to coolant additives, as well as hardening, cracking, cold leaks, and aging. The silicone hose is constructed from 1-ply reinforced nylon fiber and has been extreme duty cycle tested. Optimized hose lengths available based on the heater being installed, reducing hose waste and improving plumbing performance. Boxed or spool length available for customers needing larger volumes.

### SPECIFICATIONS

- Part Numbers\*: HH-1 for 1" (25mm) hose  
HH-3/4 for 3/4" (19mm) hose  
HH-5/8 for 5/8" (16mm) hose
- Meets or exceeds the operating requirements of SAE J20 R3 Class A
- Meets or exceeds the operating requirements of TMC RP303B Class I Grade II
- Standard wall thickness of 0.140" / 0.170"
- Working pressure 1/3 of burst pressure
- Bend radius 5 times the ID of the hose
- Resists hardening, cracking, cold leaks, aging, and many chemicals.

\*Contact sales for additional hose sizes.

### CUSTOM ENGINEERED TO WITHSTAND:



COOL TEMPS



HOT TEMPS



OIL SPLASH  
RESISTANCE



OZONE  
RESISTANT



DIRECT  
SUNLIGHT

- ✓ **Boxed, spool, or custom lengths available**
- ✓ **Extreme temperature resistance**
- ✓ **Superior flexibility**
- ✓ **Extreme duty cycle tested for hostile engine environments**
- ✓ **Durable construction**
- ✓ **Resistant to coolant additives**

### TEMPERATURE RANGE:

